

# S40ME-B

Bore : 400 mm

Stroke : 1770 mm

Layout points		L1	L2	L3	L4
Speed	min <sup>-1</sup>	146	146	124	124
mep	MPa	2.10	1.68	2.10	1,68
Cylinder	Power				
5S40ME-B	kW	5,675	4,550	4,825	3,850
	BHP	7,725			
6S40ME-B	kW	6,810	5,460	5,790	4,620
	BHP	9,270			
7S40ME-B	kW	7,945	6,370	6,755	5,390
	BHP	10,815			
8S40ME-B	kW	9,080	7,280	7,720	6,160
	BHP	12,360			

## Specific Fuel Oil Consumption (SFOC)

g/kW·h	178.5	173.4	178.5	173.4
g/BHP·h	131.3			

## Lubricating and Cylinder Oil Consumption

Lubricating oil	3 - 4 kg/cyl.·day	(guidance value)
Cylinder oil	refer item "Specific Cylinder Oil Consumption"	

## Main Dimensions and Masses

Cyl. No		5	6	7	8
Dry Mass ton		111	127	142	156
L mm		5,000	5,700	6,400	7,100
A mm		7,376	7,376	7,376	7,376
B mm		6,426	6,426	6,426	6,426
C mm		950	950	950	950
D mm		2,590	2,590	2,590	2,590
E mm		700	700	700	700
H1 mm		8,100	8,100	8,100	8,100
H2 mm		7,700	7,700	7,700	7,700

